

## GL Flow Totalizers Series 101



### GENERAL SPECIFICATIONS

Display:	Large LCD 3.5 " x 1.5 " , with seven 5/8" and eleven 5/16" digits.
Control Buttons:	Three touch buttons on U.V. resistant polyester keypad.
Casing:	High Impact, U.V. resistant, flameproof ABS – IP67 (>NEMA4X).
Dimensions:	5 1/8" (130) x 4 1/2 " (114) x 2 3/4 " (71) l x h x d (mm)
Operating Temp.:	-20 to 70 °C (-4 to +158 °F)
Configuration:	Configuration is done at SET UP level.
Password:	All settings can be password protected.
Data Protection:	EEPROM back up of all settings. Accumulated Total backed up every minute.
Selectable Units:	TOTAL: USGAL, bbl (barrels), L, m3, kg, lb or no unit in 5/8" digits. FLOWRATE: USGAL, bbl (barrels), cf, L, m3, kg, lb or no unit in 5/16" digits TIME UNITS: second / minute / hour / day.
Environment:	EMC compliant per EN50081 and EN50082.

### MODELS

#### 101 Totalizer and Flow Rate Indicator

Features:	Totalizer and Flow Rate indication with Linearization.
Power:	3 V Lithium Battery (average life 5 years); 8 – 28 V ac/dc supply can also be used.
Information:	Total, Flow Rate, Accumulated Total and measurement units # Total can be reset to zero. Accumulated Total is not resettable

**101I Suitable for Hazardous Area Installation. Eex ia IIC T4.**



JLC International, Inc.  
958 Town Center  
New Britain, PA 18901

Phone: (800)-599-4732  
(215)-340-2650  
Fax: (215)-340-3670

[www.jlcinternational.com](http://www.jlcinternational.com)

[jlcusa@jlcinternational.com](mailto:jlcusa@jlcinternational.com)

## **101A Totalizer and Flow Rate Indicator with Analogue and Pulse output**

Features: Totalizer and Flow Rate indication with Linearization.  
4 – 20 mA output in relation to Flow rate.  
Pulse output in relation to Accumulated Total.

Power: 3 V Lithium Battery (average life 5 years); 8 – 28 V ac/dc supply  
or 4 – 20 mA loop (28 V max) can be used.

Information: Total, Flow Rate, Accumulated Total and measurement units.  
# Total can be reset to zero. Accumulated Total is not resettable.

**101A Suitable for Hazardous Area Installation. Eex ia IIB T4.**

## **101B Totalizer and Batch Controller with Pulse output**

The operator can enter a preset batch value easily or execute repeated batches. During the batch run, the preset batch value is displayed as well as the batched quantity and units of measurement. An overrun correction ensures an accurate batch quantity. The running batch quantity (5/8" digits) can be set to count up or down. Two transistor outputs are available for either 1) pulse output and one-stage batch control or 2) two-stage batch control.

Features: Preset Batch Value indication.  
Overrun correction.  
Pulse output mirroring count on display.  
One or Two-stage batch control.

Power: 3 V Lithium Battery (average life 5 years); 8 – 28 V AC/DC supply

Information: Preset Batch Value, Quantity Batched, Total, Accumulated Total and measurement units.  
# Total can be reset to zero. Accumulated Total is not resettable.

**101B Suitable for Hazardous Area Installation. Eex ia IIB T4.**

## **101C Totalizer and Flow Rate Indicator with Alarm outputs**

Features: Totalizer and Flow Rate indication  
High and Low Alarm Flow rate Monitoring  
Two Alarm Outputs  
4 – 20 mA output in relation to Flow rate.

Power: 3 V Lithium Battery (average life 5 years); 8 – 28 V AC/DC supply

Information: Total, Flow Rate, Accumulated Total, Alarm Points and measurement units  
# Total can be reset to zero. Accumulated Total is not resettable

**101C Suitable for Hazardous Area Installation. Eex ia IIB T4.**



JLC International, Inc.  
958 Town Center  
New Britain, PA 18901

Phone: (800)-599-4732  
(215)-340-2650  
Fax: (215)-340-3670

[www.jlcinternational.com](http://www.jlcinternational.com)

[jlcusa@jlcinternational.com](mailto:jlcusa@jlcinternational.com)

